




**Technische Daten**

Betriebsspannung:	3V DC
Batterietyp:	2 x LR 06 (AA)
Schutzart:	IP 20
Zulässige Umgebungstemperatur:	0°C bis +55°C
Funkfrequenz:	868 MHz-Band
Maße in mm:	L 150 x B 51 x H 26


**Technical data**

Operating voltage:	3V DC
Battery type:	2 x LR 06 (AA)
Ingress protection:	IP 20
Permissible ambient temperature:	0°C to +50°C
Radio frequency:	868 MHz band
Dimensions in mm:	L 150 x W 51 x H 26

**Einsatzbereiche:**



**Range of application:**



**Eigenschaften:**

- 15 Kanal-Funkhandsender
- 5 Gruppenkanäle + 1 Zentralkanal
- Status-LED-Anzeige
- Farbe: weiss
- Select-Taste für Hand-/Automatik-Umschaltung mit LED-Anzeige und Display-Symbolen
- Lerntaste auf der Rückseite
- Mehrere Sprachen wählbar mit beleuchtetem Display
- Werksseitig voreingestellt
- Komfortable Bedienung und Kanalwahl per Joystick
- Handelsübliche Batterien

**Product features:**

- 15 channel radio hand-held transmitter
- 5 group channels + 1 central channel
- Status-LED-Display
- color: white
- Select-button for manual/automatic switch with LED-Display and symbols on the display
- Programming push-button on the back
- Various languages for selection with illuminated display
- Factory preset
- Convenient control and selection of channels per joystick
- Takes standard batteries