



**Technische Daten**

Betriebsspannung:	3V DC
Batterietyp:	CR 2032
Schutzart:	IP 20
Zulässige Umgebungstemperatur:	0°C bis +55°C
Montageart:	Aufputz durch Wandhalterung (inkl.)
Funkfrequenz:	868 MHz-Band

**Technical data**

Operating voltage:	3V DC
Battery type:	CR 2032
Ingress protection:	IP 20
Permissible ambient temperature:	0°C to +55°C
Type of installation:	Surface mount via included wall holder
Radio frequency:	868 MHz band

**Einsatzbereiche:**



**Eigenschaften:**

- 1 Kanal-Wandsender
- Große AUF-STOPP-AB Tasten
- Lüftungs- und Wendeposition
- Einfache Befestigung mit Wandhalterung
- Sendekontroll-LED
- Handelsübliche Knopfatterie
- Passend für alle gängigen Schalterprogramme (mit Adapterrahmen)
- Select-Taste für Hand-/Automatik-Umschaltung
- Volle Abwärtskompatibilität zu unidirektionalen elero-Funkprodukten

**Range of application:**



**Product features:**

- 1 channel wall sender
- Large UP-STOP-DOWN push-buttons
- Ventilation and tilting position
- Easy to attach with wall mounting
- LED for transmission control
- Takes standard button cell battery
- Suitable for all current switch programmes (with adapter frame)
- Select-button for manual/automatic switch
- Full downwards compatibility with unidirectional radio products by elero