




Technische Daten

Betriebsspannung:	3V DC
Batterietyp:	2 x LR 06 (AA)
Schutzart:	IP 20
Zulässige Umgebungstemperatur:	0°C bis +50°C
Funkfrequenz:	868 MHz-Band
Maße in mm:	L 120 x B 51 x H 26


Technical data

Operating voltage:	3V DC
Battery type:	2 x LR 06 (AA)
Ingress protection:	IP 20
Permissible ambient temperature:	0°C to +50°C
Radio frequency:	868 MHz band
Dimensions in mm:	L 120 x W 51 x H 26

Einsatzbereiche:



Range of application:



Eigenschaften:

- 5 + 1 Kanal-Funkhandsender
- Status-LED-Anzeige
- Verschiedene Farben:
reinweiß, silber, titangrau
- Select-Taste zur Hand-/Auto-/Kanal-Umschaltung
mit LED-Anzeige
- Lerntaste auf der Rückseite
- Kanalanzeige über Ring mit 5 LED's
- Beschriftungsaufkleber für die Rückseite
- Handelsübliche Batterien
- Volle Abwärtskompatibilität zu unidirektionalen
elero-Funkprodukten

Product features:

- 5 + 1 channel radio hand-held transmitter
- Status-LED-Display
- Different colors:
white, silver, titanium grey
- Select-button for manual/automatic/command switch
with LED-Display
- Programming push-button on the back
- Display of command via 5 LEDs
- Sticker for individual labeling on the back
- Takes standard batteries
- Full downwards compatibility with unidirectional radio
products by elero